

Model 27000 Holding Tank – 2 Piece Unit
 Balancing Capacity 24,070 Litres

- This tank design is installed in multiple units.
- Each unit has a Tongue and groove design and is sealed with a fibrous mastic sealant.
- Tanks are cast with 35 MPA strength concrete at 7 days with 5 - 7% air.
- Steel reinforced with 20m Rebar, spaced at 300mm each direction at 50 mm cover. CAN/CSA-G30.18
- Tanks conform to National Standards of Canada CAN/CSA B66-05.
- Non sulphate resistant concrete.
- Standard 3 inlets.


Notes

- 1: 75mm Pipe cast in top of lid for access to any electrical cords.
- 2: 610 x 610 partition knock-out.
3. Water storage capacity to under side of top..... **29,609 Ltrs.**
4. Cast in place 24"ID plastic riser with plastic lid secured with stainless steel fasteners extending 100mm above top of tank.
5. 750mm high float tree available upon request.

To ensure water-tight seal, it is recommended that the joint be grouted both inside and out.
 Recommended for ONE METRE burial over top of tank, away from any vehicular traffic. Two metre burial tanks are available upon request.

Top Half Weight 14515 kg
 Bottom Half Weight .. 14515 kg
 Total Tank Weight 29030 kg

Tank markings observed:
 Inlet & outlet
 Marked on tank top



NPCP 2007
 27000
 HOLDING
 BD 1M
 WC 24070
 NON-SUL
 AGINP
 PML

