

NEWMARKET PRE-CAST CONCRETE PRODUCTS

Telephone: 905-852-6111 ; Toll Free 1-800-263-1297

Model 22500 (5000) Holding Tank Low Profile Balancing Capacity 19980 (4395gal)

- This tank design is installed for wet or rock conditions.
- Tanks are cast with 35 MPA strength concrete at 7 days with 5 - 7% air.
- Steel reinforced with 20M Rebar, spaced 300mm apart, each direction, at 50mm cover. CAN/CSA-G30.18
- Tanks conform to National Standards of Canada CAN/CSA B66-05
- Standard 3 inlets.
- Non sulphate resistant concrete.
- Standard 3 inlets.

Bare Weight 19960 kg (44003 lb)
Lid Weight 7170 kg (15807 lb)
Total Tank Weight 27130 kg (59810 lb)

- Notes
- 1: 75mm pipe cast in top of lid for access of any electrical cords.
 2. Water storage capacity to under side of top 24,862 Ltrs. (5469gal)
 3. Cast in place 610mm ID plastic riser with plastic lids secured with stainless steel fasteners extending 100mm above top of tank.
 4. 610 x 610 knockout.
 5. 750mm high float tree available upon request.

Recommended for ONE METRE burial over top of tank, away from any vehicular traffic. Two metre burial tanks are available upon request.

Tank markings observed:
Inlet & outlet
Marked on tank top - inlet end

NPCP 2009
22500 L
HOLDING
BD 1M
WC 19980
NON-SUL
AGINP
PML

